

# L1L2-S2GRA-1 RA-1 Remote Antenna

## **KEY FEATURES**

- » Designed Specifically for Operation with the Defense Advanced GPS Receiver (DAGR)
- » L1/L2 Dual Band
- » High Out-of-Band Rejection
- » Spec Compliant Performance over Entire Environmental and Voltage Range
- » Multiple Color Options: White, Olive Green, Grey, Black, Tan
- » Flush Magnet Mount Designed to Handle Force up to 20Gs or Bolt Pattern for Attachment

1.538

» Will Work with DAGR

## INTRODUCTION

The L1L2-S2GRA-1 is a dual band active L1/L2 GPS antenna that is specifically designed for operation with the US DoD DAGR military grade receiver. The L1L2-2GRA-1 is available with an SMA connector and various radome colors. It is compact, lightweight and water resistant.

### DURABLE, HI PRECISION, BUILT TO LAST

For surface mobility, the GPS Source Mil-Spec DAGR antenna offers exceptional performance with unsurpassed reliability. Designed to support the Warfighter, the portable, yet precise GPS L1/L2 DAGR antenna receives the L1 & L2 signals. It complies with all RA-1 electrical specifications.



GPS Source, Inc. | bpaul@gpssource.com | (866) 289-4777 toll free (in U.S.) | +1 (719) 565-8589



## **L1L2-S2GRA-1 RA-1** Remote Antenna

### L1/L2 DAGR Mil Spec GPS Antenna

| Operating Frequencies   | L1 (1575.42MHz)<br>Bandwidth +/- 15MHz<br>L2 (1227.60MHz)<br>Bandwidth +/- 15MHz |
|---|--|
| Polarization  | RHCP   |
| Element Gain (Active) at 4 ft G.P.                                | L1 3dBiC min.<br>L2 3dBiC min.   |
| Axial Ratio   | 2dB max  |
| LNA Gain Output = 50Ω   | L1: 30dB min.<br>L2: 30dB min.   |
| LNA DC Power  | 2.5 - 16 VDC (35 mA max)   |
| Noise Figure  | 3dB max  |
| LNA OP1dB Compression   | 8dBm   |
| LNA OIP3  | 20dBm  |
| Rejection @ +/- 50MHz (Active)<br>Rejection @ +/- 100MHz (Active) | >12dB<br>>42dB   |
| Out Impedence   | 50Ω  |
| SWR   | 2.0:1  |
| Temperature   | -54°C to 71°C  |
| Altitude  | 50,000 ft  |
|   |  |

#### **Physical Specifications**

| Size        | Diameter: 2.7"<br>Height: .944" |
|-------------|---------------------------------|
| Weight      | 6.4 oz                          |
| Base Finish | Iridite per Mil-C-5441          |
| Connector   | SMA Female                      |

### **Built to Military Specifications**

Meets Mil Spec MIL-STD-810, MIL-C-5541, MIL-E-5400, MIL-1-45208A, MIL-STD-461, MIL-STD-1472, DO-160D





### **ABOUT US**

GPS Source is a 100% veteran owned, original equipment manufacturer (OEM) that designs, manufactures and sells high-precision GNSS/GPS technology for the Defense Industry.

www.gpssource.com

